

INDEPENDENT

Electric Vehicle Battery Certificate

Certificate issued by



Certificate creation time: 2026-09-24, 13:26

Certificate number: 20260924.143

Vehicle information

Registration number / VIN	Brand / Model	Odometer	Battery type	Charging port type
BSF951 / KMHK381GFLU098938	Hyundai Kona	257180 km	LIPB	CCS


Test results

Date and time of test: 2026-09-24, 09:58

Test performed by:

kvdbil

State of health (SOH)



100%

Battery capacity

Estimated capacity	63.8 kWh
Factory new capacity	64.0 kWh

WLTP range

Estimated WLTP	483 km
Factory new WLTP	484 km

Diagnostics

	MIN	MAX	DELTA
Battery temperature	9.0°C	10.0°C	1.0°C
Cell voltage	3.96V	3.98V	20mV

Cell voltages

1-24	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.980	3.960	3.980	3.980	3.980	3.960	3.960	3.980	3.960	3.960	3.960	3.960	3.960
25-48	3.960	3.960	3.960	3.960	3.960	3.960	3.980	3.960	3.960	3.980	3.960	3.980	3.960	3.980	3.980	3.980	3.980	3.980	3.980	3.960	3.980	3.980	3.980
49-72	3.980	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.980	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.980
73-96	3.980	3.960	3.980	3.980	3.980	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.960	3.980	3.980	3.960	3.980	3.980	3.960	3.980	3.960
97-98	3.980	3.980																					

Normal: Cell voltage deviation is within the expected range.

Method and control

Battery assessment is based on diagnostic data retrieved from the vehicle's OEM Battery Management System (BMS) and comparative reference data from similar vehicle models.

Attest

The test was executed according to the Optiledger SOH procedure with no known technical issues during data acquisition.

Disclaimer

Results represent an estimated assessment of battery condition at the time of testing and do not constitute a warranty or guarantee of battery capacity, performance, or remaining lifetime. The original WLTP range is determined and published by the vehicle manufacturer under standardized laboratory test conditions. The estimated WLTP presented in this report is calculated from diagnostic data and reference parameters and does not represent actual driving range. Real-world range may vary depending on driving conditions, temperature, load, and driving behavior. Full methodology, limitations and liability disclaimer available at: https://optiledger.se/legal/optiledger_battery_test_methodology_and_disclaimer.pdf.