INDEPENDENT

Electric Vehicle Battery Certificate

Certificate issued by

Optiledger

Certificate creation time: 2026-10-14, 11:19

Certificate number: 20261014.111

Vehicle information


Registration number / VIN	Brand / Model	Odometer
GAP98B / TMBJW7NP6N7014873	Skoda Superb	70600 km

Test results

Date and time of test: 2026-10-10, 08:54

Test performed by: kvdbil

State of health (SOH)



93 %

Battery capacity

Estimated capacity



Factory new capacity

WLTP range

Estimated WLTP 55 km



Factory new WLTP 59 km

Diagnostics

	MIN	MAX	DELTA
Battery temperature	13.0°C	13.5°C	0.5°C
Cell voltage	3.95V	3.972V	22mV

Cell voltages

1–24	3.955	3.955	3.956	3.956	3.960	3.960	3.969	3.970	3.969	3.970	3.969	3.970	3.972	3.969	3.969	3.968	3.970	3.966	3.969	3.968	3.968	3.970	3.968	3.969
25–48	3.960	3.959	3.953	3.953	3.953	3.954	3.967	3.968	3.968	3.969	3.968	3.968	3.968	3.968	3.966	3.968	3.969	3.968	3.966	3.966	3.966	3.966	3.966	3.967
49–72	3.953	3.952	3.959	3.958	3.951	3.952	3.967	3.968	3.967	3.966	3.966	3.967	3.966	3.965	3.965	3.966	3.965	3.965	3.950	3.950	3.951	3.951	3.956	3.956
73–96	3.954	3.953	3.954	3.953	3.957	3.959	3.968	3.965	3.968	3.968	3.969	3.968	3.969	3.968	3.969	3.968	3.969	3.968	3.968	3.968	3.968	3.968	3.968	3.969

Normal: Cell voltage deviation is within the expected range.

Method and control

Battery assessment is based on diagnostic data retrieved from the vehicle's OEM Battery Management System (BMS) and comparative reference data from similar vehicle models.

Attest

The test was executed according to the OptiLedger SOH procedure with no known technical issues during data acquisition.

Disclaimer

Results represent an estimated assessment of battery condition at the time of testing and do not constitute a warranty or guarantee of battery capacity, performance, or remaining lifetime. The original WLTP range is determined and published by the vehicle manufacturer under standardized laboratory test conditions. The estimated WLTP presented in this report is calculated from diagnostic data and reference parameters and does not represent actual driving range. Real-world range may vary depending on driving conditions, temperature, load, and driving behavior. Full methodology, limitations and liability disclaimer available at: https://optiledger.se/legal/optiledger_battery_test_methodology_and_disclaimer.pdf.

Contact us: contact@datavarde.se | sales@datavarde.se